

421* Specifications

| | |
|--------------------------------------|--|
| Minimum seat height (ADA Compliant): | Low Model 19" (48.3 cm) High Model 21" (53.3 cm) |
| Maximum seat height: | Low Model 30.5" (77.5 cm) High Model 37" (94 cm) |
| Maximum vertical elevation: | Low Model 11.5" (29.2 cm) High Model 16" (40.6 cm) |
| Section Dimensions | |
| Back Section: | 19" tapering to 13" wide x 21" long (48 cm tapering to 33 cm wide x 53 cm long) |
| Seat Section: | 19.5" wide x 19" deep (49.5 cm wide x 48 cm) |
| Foot Section: | 18" tapering to 12" wide x 23" long (45.7 cm tapering to 30.5 cm wide x 58 cm) |
| Maximum width between arms: | 19" (48 cm) |
| Maximum width w/arms: | 26" (66 cm) |
| Overall length: | |
| w/o headrest extension | 72.5" (184 cm) |
| w/headrest extension | 78.5" (199 cm) |
| Electrical Input/Power Consumption: | 115/60, 2.8 amps 230/50, 1.4 amps |
| Weight†: | 314 lbs (143 kg) |
| Shipping weight†: | 378 lbs (171 kg) |
| Shipping size†: | 80" x 32" x 34" (203 cm x 81 cm x 86 cm) |

Listed to the Safety Standards for Medical Electrical Equipment UL 60601-1, CSA-C22.2 60601-1, and IEC 60601-1.

†Weight will vary depending on options chosen.

