

423* Specifications

Minimum seat height (ADA Compliant):	Low Model 19" (48.3 cm)
	High Model 21" (53.3 cm)
Maximum seat height:	Low Model 30.5" (77.5 cm)
	High Model 37" (94 cm)
Maximum vertical elevation:	Low Model 11.5" (29.2 cm)
	High Model 16" (40.6 cm)
Section Dimensions	
Back Section:	19" tapering to 13" wide x 21" long (48 cm tapering to 33 cm wide x 53 cm long)
Seat Section:	19.5" wide x 19" deep (49.5 cm wide x 48 cm)
Foot Section:	18" tapering to 12" wide x 23" long (45.7 cm tapering to 30.5 cm wide x 58 cm)
Maximum width between arms:	19" (48.3 cm)
Maximum width w/arms:	26" (66 cm)
Overall length:	
w/o headrest extension	72.5" (184 cm)
w/headrest extension	78.5" (199 cm)
Electrical Input/Power Consumption:	115/60, 3.8 amps
	230/50, 1.9 amps
Weight†:	306 lbs (139 kg)
Shipping weight†:	370 lbs (168 kg)
Shipping size†:	80" x 32" x 34" (203 cm x 81 cm x 86 cm)

Listed to the Safety Standards for Medical Electrical Equipment UL 60601-1, CSA-C22.2 60601-1, and IEC 60601-1.

†Weight will vary depending on options chosen.

